



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS\_GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : SynPower™ DT C2 SAE 0W-30  
Synthetic Motor Oil

Product code : 875423

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

### 1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline  
Wieldrechtseweg 39  
3316 BG Dordrecht  
Netherlands  
+31 (0)78 654 3500 (in the Netherlands), or  
contact your local CSR contact person

SDS@valvoline.com

### 1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact  
your local emergency telephone number at 112

### Product Information

+31 (0)78 654 3500 (in the Netherlands), or  
contact your local CSR contact person

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### Additional advice

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 70,00 - < 80,00
Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based	72623-87-1 276-738-4 01-2119474889-13-xxxx	Asp. Tox.1; H304	>= 5,00 - < 10,00
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil- based	72623-86-0 276-737-9	Asp. Tox.1; H304	>= 5,00 - < 10,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 1,00 - < 2,50
C14-16-18 Alkyl phenol	931-468-2 01-2119498288-19-xxxx	Skin Sens.1B; H317 STOT RE2; H373	>= 1,00 - < 2,50

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

	Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

---

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: High volume water jet



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

## 5.2 Special hazards arising from the substance or mixture

- |                                      |   |   |
|--------------------------------------|---|---|
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products        | : | Nitrogen oxides (NOx)<br>carbon dioxide and carbon monoxide               |

## 5.3 Advice for firefighters

- |   |   |  |
|---|---|--|
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus. |
| Specific extinguishing methods                | : | Product is compatible with standard fire-fighting agents.      |
| Further information                           | : | Standard procedure for chemical fires.                         |

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- |                      |   |  |
|----------------------|---|--|
| Personal precautions | : | Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.<br>Comply with all applicable federal, state, and local regulations. |
|----------------------|---|--|

### 6.2 Environmental precautions

- |                           |   |   |
|---------------------------|---|---|
| Environmental precautions | : | Prevent product from entering drains.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities. |
|---------------------------|---|---|

### 6.3 Methods and material for containment and cleaning up

- |                         |   |   |
|-------------------------|---|---|
| Methods for cleaning up | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).<br>Keep in suitable, closed containers for disposal. |
|-------------------------|---|---|

### 6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

### 7.3 Specific end use(s)

- Specific use(s) : No data available

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

#### Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Skin and body protection	: Wear as appropriate: Impervious clothing Safety shoes Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: No personal respiratory protective equipment normally required.

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: amber
Odour	: oily
Odour Threshold	: No data available
pH	: Not applicable
Pour point	: < -48 °C
Boiling point/boiling range	: No data available
Flash point	: 224 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Density : ca. 0,843 g/cm<sup>3</sup> (15,6 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : < 6.000 mPa.s (-35 °C)

Viscosity, kinematic : 46,5 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

### 9.2 Other information

Self-ignition : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if stored and applied as directed.

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

### 10.4 Conditions to avoid

Conditions to avoid : None known.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents  
Strong bases

### 10.6 Hazardous decomposition products



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Hazardous decomposition products : No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

#### Acute toxicity

Not classified based on available information.

#### Components:

##### HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg  
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

#### Components:

##### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.  
Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Remarks: No mortality observed at this dose.

#### Components:

##### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

#### Components:

##### REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Remarks: No mortality observed at this dose.





# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.  
Remarks: Information given is based on data obtained from similar substances.

## Components:

### **C14-16-18 Alkyl phenol:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Assessment: Not classified as acutely toxic by ingestion under GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.  
Remarks: No mortality observed at this dose.

## **Skin corrosion/irritation**

Not classified based on available information.

## Components:

### **HEAVY PARAFFINIC DISTILLATE:**

Result: Slight, transient irritation

### **Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:**

Species: Rabbit  
Result: No skin irritation

### **Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:**

Result: No skin irritation

### **REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):**

Species: Rabbit  
Result: Mild skin irritation  
Remarks: Information given is based on data obtained from similar substances.

### **C14-16-18 Alkyl phenol:**

Method: OECD Test Guideline 431  
Result: No skin irritation

## **Serious eye damage/eye irritation**

Not classified based on available information.

## Product:

Remarks: Unlikely to cause eye irritation or injury.



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

## Components:

### HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Species: Rabbit

Result: No eye irritation

### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Result: No eye irritation

### REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

### C14-16-18 Alkyl phenol:

Species: Rabbit

Result: Slight, transient irritation

## Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

## Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

## Components:

### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

### REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

### C14-16-18 Alkyl phenol:

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

## Germ cell mutagenicity

Not classified based on available information.

### Components:

#### REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: **Ames test**  
Test species: **Salmonella typhimurium**  
Metabolic activation: **with and without metabolic activation**  
Result: **negative**

#### C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: **Ames test**  
Test species: **Salmonella typhimurium**  
Metabolic activation: **with and without metabolic activation**  
Result: **negative**

## Carcinogenicity

Not classified based on available information.

### Components:

#### Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

#### Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

## Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

Not classified based on available information.

### STOT - repeated exposure

Not classified based on available information.

### Components:

#### C14-16-18 Alkyl phenol:

Target Organs: **Liver**  
Assessment: **The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.**

## Aspiration toxicity

Not classified based on available information.

### Components:



# SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

## HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

## Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based:

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks: No data available

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

#### Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : LL50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10.000 mg/l  
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l  
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l  
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l  
Species: Aquatic invertebrates

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

	Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1.000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea) Test substance: WAF Method: OECD Test Guideline 211

### bis(nonylphenyl)amine

Toxicity to fish	: LC50 (Danio rerio (zebra fish)): > 100 mg/l Exposure time: 96 h Test Type: static test Remarks: Information given is based on data obtained from similar substances.
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test

### C14-16-18 Alkyl phenol



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Toxicity to fish	: LC50 (Cyprinus carpio (Carp)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202
Toxicity to algae	: EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

### 12.2 Persistence and degradability

#### Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

bis(nonylphenyl)amine

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 0 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

C14-16-18 Alkyl phenol

Biodegradability	: Result: Readily biodegradable. Remarks: Expert judgement
------------------	---

### 12.3 Bioaccumulative potential

#### Components:

bis(nonylphenyl)amine

Partition coefficient: n-octanol/water	: log Pow: > 7,5
--	------------------

C14-16-18 Alkyl phenol

Partition coefficient: n-octanol/water	: log Pow: > 7,2
--	------------------



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

---

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good



# **SAFETY DATA SHEET**

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

## **14.5 Environmental hazards**

Not regulated as a dangerous good

## **14.6 Special precautions for user**

Not applicable

## **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

---

## **SECTION 15: Regulatory information**

### **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable





## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

---

**The components of this product are reported in the following inventories:**

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: Not in compliance with the inventory
TSCA	: On TSCA Inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**15.2 Chemical safety assessment**

No data available

---

**SECTION 16: Other information**

**Further information**

Internal information : 000000266380

**Full text of H-Statements**

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor  
Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement

PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value



## SAFETY DATA SHEET

SynPower™ DT C2 SAE 0W-30 Synthetic Motor  
Oil

Version: 3.0

Revision Date: 02.07.2020

Print Date: 19/09/2022

---

TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands  
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.  
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine  
CLP : Classification, Labelling and Packaging  
CSA : Chemical Safety Assessment  
CSR : Chemical Safety Report  
DNEL : Derived No Effect Level.  
EINECS : European Inventory of Existing Commercial Chemical Substances.  
ELINCS : European List of Notified Chemical Substances  
PEC : Predicted Effect Concentration  
PEL : Permissible Exposure Limits  
PNEC : Predicted No Effect Concentration  
R-pharse : Risk phrase  
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals  
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail  
S-pharse: Safety phrase  
WGK : German Water Hazard Class